



CK1100、CK800数控车床

CNC LATHE



CK630数控车床

CNC LATHE



技术参数 TECHNICAL SPECIFICATION		
型号(Model)	CK800	CK1100
床身上最大回转直径 Max.swing over bed	800mm	1100mm
刀架上最大回转直径 Max.swing over slide	520mm	780mm
床身导轨宽度 Width of bed	550mm	
最大工件长度 Max.length of the work-piece	1000mm, 1500mm, 2000mm, 3000mm	
主轴转速 Range of the speed	10~800r/min (四档无限变速 4 gear stepless)	9.5~750r/min (四档无限变速 4 gear stepless)
主轴孔径 Spindle bore	Φ100mm	
主轴锥孔 Taper of bore in spindle	1:20	
X轴行程 Travel (X Axis)	480mm	420mm
Z轴行程 Travel (Z Axis)	850 / 1350 / 1850 / 2850mm	
快速移动速度 Rapid traverse rate	X:3800mm/min Z:7500mm/min	
最小进给单位 Min.feed unit	X:0.0005mm Z:0.001mm	
进给电动机 Feed motor	交流伺服电机 Servo motor	
主电动机功率 Main motor power	11kw 变频 (frequency conversion)	
数控系统 CNC system	广州 GSK980 也可根据客户要求进行配置 (Also change the system according to the user's option)	
刀架 Tool post	4工位电动刀架 4 station electric tool carrier	
机床净重 Net weight	4.2t, 5.2t, 5.8t, 6.2t	5.2t, 5.8t, 6.0t, 6.8t
机床外形尺寸 Overall dimensions	长 L(mm)	3100, 3600, 4100, 5100
	宽 W(mm)	1750
	高 H(mm)	1880

技术参数 TECHNICAL SPECIFICATION		
型号	Model	CK630
床身上最大回转直径	Max.swing over bed	630mm
刀架上最大回转直径	Max.swing over tool-post	300mm
床身导轨宽度	Width of bed	550mm
最大工件长度	Max.length of the work-piece	1000mm, 1500mm, 2000mm, 3000mm
主轴转速	Range of the speed	12.5~1000r/min(四档无限变速 4 gear stepless)
主轴孔径	Spindle bore	Φ100mm
主轴锥孔	Taper of bore in spindle	1:20
X轴行程	Travel (X Axis)	480mm
Z轴行程	Travel (Z Axis)	850 / 1350 / 1850 / 2850mm
快速移动速度	Rapid traverse rate	X:3800mm/min Z:7500mm/min
最小进给单位	Min.feed unit	X:0.0005mm Z:0.001mm
进给电动机	Feed motor	交流伺服电机 Servo motor
主电动机功率	Main motor power	11kw 变频 (frequency conversion)
数控系统	CNC system	广州 GSK980 也可根据客户要求进行配置 (Also change the system according to the user's option)
刀架	Tool post	4工位电动刀架或棒刀 4 station electric tool carrier
机床净重	Net weight	4.2t, 4.8t, 5.1t, 5.8t
机床外形尺寸 [长×宽×高]	Overall dimensions(L×W×H)	3100/3600/4100/5100×1750×1880